



EcoGreen Technologies (S) Pte Ltd

Block 10 Ubi Crescent # 05-21 Ubi Techpark Singapore 408564
 Tel: (65) 6853 3368 Fax: (65) 6853 3386 Email: ecogreentech@ecogreens.com.sg



Thermocouple Wire - T Type, Duplex Insulated

GG-T, TG-T, TT-T FF-T, PR-T Series

- ✔ High Quality Type "T" Thermocouple Grade Wire
- ✔ In Stock - Available for Immediate Shipment
- ✔ Choice of Insulation, Wire Gage, & Length



ANSI Color Code: Positive Wire, Blue; Negative Wire, Red; Overall, Brown

The "To Order" box contains some examples of popular models. Use the "Part Number Builder" (Below Table) to get pricing for all available models. Use the table below as a guide for available types

Insulation1	AWG No.	Model Number	Type Wire	Insulation		Max. Temp		Nominal Size	Wt. † lb/1000'
				Conductor	Overall	°F	°C		
Glass	20	GG-T-20	Solid	Glass Braid	Glass Braid	500	260	.060 x .095	9
	20	GG-T-20S	7 x 28	Glass Braid	Glass Braid	500	260	.060 x .100	9
	24	GG-T-24	Solid	Glass Braid	Glass Braid	400	200	.050 x .080	5
	24	GG-T-24S	7 x 32	Glass Braid	Glass Braid	400	200	.050 x .085	5
	26	GG-T-26	Solid	Glass Braid	Glass Braid	400	300	.045 x .075	4
	28	GG-T-28	Solid	Glass Braid	Glass Braid	400	300	.045 x .070	3
	30	GG-T-30	Solid	Glass Wrap	Glass Braid	300	150	.045 x .070	3
	30	TG-T-30	Solid	Teflon	Glass Braid	300	150	.034 x .047	2
	36	TG-T-36	Solid	Teflon	Glass Braid	300	150	.028 x .038	2
	Teflon® Glass	40	TG-T-40	Solid	Teflon	Glass Braid	300	150	.026 x .035

EcoGreen Technologies (S) Pte Ltd

Block 10 Ubi Crescent # 05-21 Ubi Techpark Singapore 408564
 Tel: (65) 6853 3368 Fax: (65) 6853 3386 Email: ecogreentech@ecogreens.com.sg

	20	TT-T-20	Solid	PFA	PFA	500	260	.068 x .116	11
		TT-T-	7 x					.073 x	
	20	20S	28	PFA	PFA	500	260	.126	11
		TT-T-	7 x					.065 x	
	22	22S	30	PFA	PFA	500	260	.133	9
		TT-T-	7 x					.056 x	
	24	TT-T-24	Solid	PFA	PFA	400	200	.092	7
		TT-T-	7 x					.063 x	
	24	24S	32	PFA	PFA	400	200	.102	7
		TT-T-	7 x					.024 x	
	30	30††	Solid	PFA	PFA	300	150	.040	2
		TT-T-	7 x					.019 x	
	36	36††	Solid	PFA	PFA	300	150	.030	2
		TT-T-	7 x					.017 x	
Teflon® Neoflon, PFA (High performance)	40	40††	Solid	PFA	PFA	300	150	.026	2
T	20	FF-T-20	Solid	FEP	FEP	392	200	.068 x .116	11
eflon® Neoflon FEP	24	FF-T-24	Solid	FEP	FEP	392	200	.056 x .092	7
	24	PP-T-24	Solid	Polyvinyl	Polyvinyl	221	105	.075 x .120	10
		PP-T-	7 x					.080 x	
	24	24S	32	Polyvinyl	Polyvinyl	221	105	.130	10
Polyvinyl	24	PR-T-24	Solid	Polyvinyl	(Rip Cord)**	221	105	.050 x .086	5

†Weight of spool and wire rounded up to the next highest lb. (does not include packing material)

**Two insulated leads bonded together, but with no overwrap

††Overall color clear

Note: The thermocouple wire come in standard length in roll of 500ft and 1,000ft. And cut length of 1meter, 2meter.

Further Inquiry, Please contact:

EcoGreen Technologies (S) Pte Ltd

Block 10 Ubi Crescent #05-21
 Ubi Techpark Singapore 408564
 Tel: (65) 6853 3368 Fax: (65) 6853 3386
E-Mail: ecogreentech@ecogreens.com